



D

Strahlerelement aus Aluminium in 4 Farbvarianten, 365° dreh- und 35° schwenkbar
 Drehbarkeit durch patentiertes Verriegelungssystem sperrbar
 Werkzeugloser Einbau in verschiedenen Montagesets durch Kugelschnappsystem
 Effizientes COB Modul, lieferbar in 2700K|3000K|4000K und Colour Warm Dimming
 Hohe Lichtströme und passive Kühlung durch optimiertes Kühlkörperdesign
 Wechselreflektor in verschiedenen Ausstrahlwinkeln erhältlich
 Zubehör werkzeuglos einsetzbar: Ausblendtubi, Linsen, Wabenraster, Farbfilter
 Inkl. Konverter dimmbar über Phasen-/ abschnitt oder optional mit DALI Signal

E

Strahlerelement aus Aluminium in 4 Farbvarianten, 365° dreh- und 35° schwenkbar
 Turn can be locked using patented fastening system
 Toolless mounting in various mounting sets using ball-snap system
 Efficient COB module, available in 2700K|3000K|4000K and Colour Warm Dimming
 High luminous flux and passive cooling thanks to optimised heat sink design
 Changeable reflector available in various beam angles
 Toolless inst. of: anti-glare adapter, lenses, honeycomb louvers, colour filters
 Incl. converter dimmable via phase fired control or optionally via DALI signal

F

Strahlerelement aus Aluminium in 4 Farbvarianten, 365° dreh- und 35° schwenkbar
 Rotation pouvant être bloquée par système de verrouillage breveté
 Encastrage sans outil dans divers sets de montage par système de loquet à billes
 Module COB efficient, livrable en 2700K|3000K|4000K et Colour Warm Dimming
 Flux lumineux élevés et refroidissement passif par design optimisé du radiateur
 Réflecteur amovible disponible en différents angles de rayonnement
 Acc. encastr. ss outil: tube anti-éblouist, lentilles, grilles alv., filt. coul.
 Convertisseur dimm. p coupure phase amont/aval incl. ou en opt* av. signal DALI

INSET			
		<p>SASSO+ MIDI FLUSH</p> <p>TYPE</p> <p>13W LED 1000 lm* 18W LED 1400 lm* 25W LED 1900 lm*</p> <p>CODE</p> <p>048-2#10### 048-2#11### 048-2#12###</p> <p>COB LED 220-240V</p>	
COLOUR RENDERING INDEX			
CRI 80	CRI 90	<p>048-1... CRI 80 048-4... CRI 90 (only 2700K 3000K)</p>	
LED COLOUR TEMPERATURE			
1600-3000K	2700K	3000K	4000K
			<p>048-0... 1600-3000K (only 18W) 048-4... 2700K 048-5... 3000K 048-6... 4000K</p>
CONTROL			
non DIM	phase-cut DIM	DIM DALI	<p>048-1... non DIM / phase-cut DIM* 048-3... DIM DALI</p> <p>*phase-cut DIM only for 13W 25W</p>
COLOUR			
			<p>048-6... grey 048-7... white 048-8... black 048-9... gold</p>
REFLECTOR			
			<p>048-S... spot 15° 048-M... medium 25° 048-F... flood 44°</p>
REFLECTOR WLS			
			<p>048-S... spot 13° 048-M... medium 24° 048-F... flood 36°</p>

MOUNTING FLUSH			
	<p>116</p> <p>18-25</p> <p>ø 105</p>	<p>MOUNTING SET TRIMLESS for installation in plasterboard ceilings</p> <p>TYPE</p> <p>trimless mounting set</p> <p>CODE</p> <p>052-1921447</p>	
	<p>108</p> <p>2-25</p> <p>ø 112</p>	<p>MOUNTING RING WITH TRIM ROUND for intermediate ceilings</p> <p>COLOUR</p> <p>white black gold</p> <p>CODE</p> <p>052-1922447 052-1922448 052-1922449</p>	
	<p>108</p> <p>2-25</p> <p>112 112</p>	<p>MOUNTING RING WITH TRIM SQUARE for intermediate ceilings</p> <p>COLOUR</p> <p>white black</p> <p>CODE</p> <p>052-1942417 052-1942418</p>	
ACCESSORY			
	<p>111</p> <p>ø 74</p> <p>25</p> <p>ø 74</p> <p>25</p> <p>ø 74</p>	<p>SNOOT</p> <p>TYPE</p> <p>short snoot with glass long snoot with glass long snoot without glass</p> <p>CODE</p> <p>048-219131# 048-219121# 048-219111#</p>	
	<p>160</p> <p>130</p> <p>230 230</p>	<p>MOUNTING HOUSING for exposed concrete</p> <p>TYPE</p> <p>mounting housing</p> <p>CODE</p> <p>052-1913410</p> <p>I use not for offset version</p>	
COLOUR			
			<p>048-6... grey 048-7... white 048-8... black 048-9... gold</p>

► BAVARIA LOUNGE, MUNICH
Architect: Tina Aßmann, Munich
Lighting design:

